

TAB H100 HE

Display for weighing systems and industrial application.



Suitable as

- **REPEATER** with serial connection
- **MEASURE UNIT** for direct connection to the load cell.

TECHNICAL FEATURES

Working Temperature: -10 ÷ 40°C

Voltage Supply: 230 V ac / 110 V ac 50 Hz / 48 Vac

Power consumption: 25 VA

Serial Connection (as **Repeater** version): Rs232 and Rs 485

Connection to load cell (as **Measure Unit** execution): 4 wires

Connection by Connector plugs

Fully settable by Radio Remote Control (in **Measure Unit** execution)

Voltage supply to load cell: 5Vdc/80 mA (Max 4 load cells x 350 ohm)

Display with nr.5 LED digit height 100 mm with automatic lighting adjustment

Visibility range: 30 meters

Protection degree: IP 55

Case: Stainless Steel

Internal Divisions: 50.000

Standard applied: EN50081-1; EN50082-2; EN 61010-1

Mounting: by nr.4 holes diameter 6 mm with distances 510 mm (horizontal) x155 mm

Dimensions: 530x190x115 mm

CAMI S.R.L.

MEASUREMENT INSTRUMENTS

Via Alessandrini, 2 - 20090 TREZZANO S/N (MI)

Tel. 02 4840 0166 - Fax 02 4840 1905

www.cami-it.com - e-mail info@cam-i.com